



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name	Platinum Extreme Duty Gloss
Chemical Name	Not Available
Other means of identification	Not Available
Product Type	Acrylic Resin

1.2 Uses and uses advised against

Use(s) Coatings Applications

1.3 Details of the supplier of the product

Supplier name	Premium Sealers
Address	Unit 1/5 Edison Circuit, Forrestdale, WA 6112, AUSTRALIA
Telephone	1800 779 007
Email	ask@sealers.com.au
Website	http://www.sealers.com.au

1.4 Emergency telephone number(s)

Emergency 1800 779 007

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

* THIS PRODUCT IS CLASSIFIED IN ACCORDANCE TO AUSTRALIAN REGULATION - GHS V3, AND ADG CODE.

GHS classification(s)	FLAMMABLE LIQUIDS: Category 3 ACUTE TOXICITY - DERMAL: Category 4 ACUTE TOXICITY - INHALATION: Category 4 SKIN CORROSION/IRRITATION: Category 2 EYE DAMAGE/IRRITATION: Category 2A STOT SINGLE EXPOSURE: Category 3 (respiratory tract irritation) HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD: Category 2 HAZARDOUS TO THE AQUATIC ENVIRONMENT - LONG-TERM HAZARD: Category 2
------------------------------	---

2.2 Label elements

Signal word **WARNING**

Pictogram(s)



Hazard statement(s)

H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statement (s)

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

Precautionary statement – Prevention

PRODUCT NAME Platinum Extreme Duty Gloss

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

P370+P378:	In case of fire: Use carbon dioxide, dry chemical or foam to extinguish. Alcohol resistant foam is preferred. If not available normal foam can be used.
P312:	Call a POISON CENTER/doctor if you feel unwell.
P391:	Collect spillage.
P302+P352:	IF ON SKIN: Wash with plenty of water.
P303+P361+P353:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P362+P364:	Take off contaminated clothing and wash it before reuse.
P332+P313:	If skin irritation occurs: Get medical advice/attention.
P304+P340:	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.
P337+P313:	If eye irritation persists: Get medical advice/attention.

Precautionary statement – Storage

P403+P235:	Store in a well-ventilated place. Keep cool.
P403+P233:	Store in a well-ventilated place. Keep container tightly closed.
P405:	Store locked up.

Precautionary statement – Disposal

P501	Dispose of contents/container to an approved waste disposal plant.
------	--

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Substance/mixture	:	Mixture
Chemical name	:	Not available
Other means of identification	:	Not available

Hazardous ingredient name	CAS Number	% by weight
XYLENE	1330-20-7	>=30 - <50
Solvent naphtha (petroleum), light arom.	64742-95-6	>=10 - <30

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

4. FIRST AID MEASURES**4.1 Description of first aid measures**

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Get medical attention immediately.
-------------------	--

PRODUCT NAME Platinum Extreme Duty Gloss

Ingestion Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention immediately.

Skin contact Flush contaminated skin with plenty of water. Continue to rinse for at least 10 minutes. Get medical attention.

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 10 minutes. Get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Inhalation Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Ingestion Can cause central nervous system (CNS) depression.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Over-exposure signs/symptoms

Inhalation Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Skin Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations

Eyes Adverse symptoms may include the following: pain or irritation watering redness

4.3 Immediate medical attention and special treatment needed

Specific treatments No specific treatment.

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Protection of first aid personnel No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11).

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable: Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable: Do not use water jet.

Specific hazards arising from the chemical: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products: No specific data.

Special precautions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark: Not available

Hazchem code: HAZCHEM: *3Y

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.2 Methods of cleaning up

Small spill Stop leak if without risk. Dilute with water and mop up if water- soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

Large spill Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas. Use spark-proof tools and explosion - proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Put on appropriate personal protective equipment (see section 8 of SDS). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

7.2 Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.3 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters Occupational Exposure standards

Ingredient name	Exposure limits
Xylene	NOHSC (1995-05-01) Short Term Exposure Limit (STEL) 655 mg/m ³ 150 ppm Time Weighted Average (TWA) 350 mg/m ³ 80 ppm

Recommended monitoring procedures: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

8.2 Individual protection measures

- Hygiene measures:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hand protection:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Eye protection:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Color	Clear
Odor	Hydrocarbon solvent-like
Odor threshold	Not available
pH	Not determined
Melting point	Not determined
Boiling point	157 °C (315 °F)
Flash point	24 °C (75 °F)
Burning rate	Not available
Burning time	Not available
Evaporation rate	Not determined
Flammability (solid, gas)	Not available
Lower and upper explosive (flammable) limits	Lower: 0.9 %(V) Upper: 7.7 %(V)
Vapor pressure	7.5 mm Hg
Vapor density	Not available
Relative density	Not available
Solubility	Not available
Solubility in water	Not available
Partition coefficient n- octanol/water	Not determined
Auto-ignition temperature	Not available
Decomposition temperature	Not available

PRODUCT NAME Platinum Extreme Duty Gloss

SADT

Viscosity Dynamic: 75 cPs
Kinematic Not available
Other information No additional information.

10. STABILITY AND REACTIVITY

Chemical stability: The product is stable.
Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Inhalation Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Ingestion Can cause central nervous system (CNS) depression.
Skin contact Causes skin irritation.
Eye contact Causes serious eye irritation.

11.2 Symptoms related to the physical, chemical and toxicological characteristics

Inhalation Adverse symptoms may include the following: respiratory tract irritation
Coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths
skeletal malformations
Skin contact Adverse symptoms may include the following: irritation redness reduced fetal weight increase
in fetal deaths skeletal malformations
Eye contact Adverse symptoms may include the following: pain or irritation watering redness

11.3 Delayed and immediate effects and also chronic effects from short and long term exposure Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Xylene				
	LD50 Oral	Rat	4,300 mg/kg	-
	LC50 Inhalation	Rat		4 h
Solvent naphtha (petroleum), light arom.				
	LD50 Oral	Rat	8,400 mg/kg	-
	LD50 Oral	Rat	8,400 mg/kg	-

Conclusion/Summary : Not available

11.4 Irritation/Corrosion

Conclusion/Summary
Skin: Not available
Eyes: Not available
Respiratory: Not available

11.5 Sensitization

Conclusion/Summary
Skin: Not available
Respiratory: Not available

11.6 Potential chronic health effects

Conclusion/Summary
General: Causes damage to organs through prolonged or repeated exposure:
Carcinogenicity: No known significant effects or critical hazards.

PRODUCT NAME Platinum Extreme Duty Gloss

Mutagenicity: No known significant effects or critical hazards.
Teratogenicity: May damage the unborn child.
Developmental effects: No known significant effects or critical hazards.
Fertility effects: May damage fertility.

11.7 Chronic toxicity

Conclusion/Summary: Not available

11.8 Carcinogenicity

Conclusion/Summary: Not available

11.9 Mutagenicity

Conclusion/Summary: Not available

11.10 Teratogenicity

Conclusion/Summary: Not available

11.11 Reproductive toxicity

Conclusion/Summary: Not available

11.12 Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light arom.	Category 3 Category 1		Respiratory tract irritation Narcotic effects lungs central nervous system (CNS)
Xylene	Category 3 Category 1		Respiratory tract irritation Narcotic effects central nervous system (CNS) liver kidneys

11.13 Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Xylene	Category 1		respiratory tract central nervous system (CNS)
Solvent naphtha (petroleum), light arom.	Category 1		skin

11.14 Numerical measures of toxicity Acute toxicity estimates

Route	ATE value
Dermal	2,286 mg/kg

Other information: Not available

12. ECOLOGICAL INFORMATION

12.1 Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
Xylene	Acute LC50 13.4 mg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 3.3 mg/l Fresh water	Fish - Rainbow trout,donaldson trout	96 h

12.2 Persistence/degradability

Conclusion/Summary : Not available

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Xylene	3.16	-	low

12.4 Mobility in soil

Soil/water partition coefficient (KOC) : Not available

Other adverse effects : No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

13.1 Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

Regulatory information	UN/NA number	Proper shipping name	Classes/Packing group
ADG	1866	RESIN SOLUTION, flammablecontains (Xylene, Solvent naphtha (petroleum), light arom.)	3 III
ADR	1866	RESIN SOLUTION, flammable contains (Xylene, Solvent naphtha (petroleum), light arom.)	3 III
ICAO/IATA	1866	RESIN SOLUTION, flammable contains (Xylene, Solvent naphtha (petroleum), light arom.)	3 III
IMO/IMDG	1866	RESIN SOLUTION, flammable contains (Xylene, Solvent naphtha (petroleum), light arom.)	3 III

Emergency Action Code : HAZCHEM: *3Y

ERG Number : 14

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

15.2 Control of Scheduled Carcinogenic Substances

Not available

Australia inventory (AICS) : All components are listed or exempted.

15.3 International Regulations

International lists : Canada inventory All components are listed or exempted.
Japan inventory Not determined.
China inventory (IECSC) All components are listed or exempted. Korea inventory All components are listed or exempted.
New Zealand Inventory (NZIoC) All components are listed or exempted. Philippines inventory (PICCS) All components are listed or exempted. United States inventory (TSCA 8b) All components are listed or exempted. Taiwan inventory (CSNN) Not determined.

16. OTHER INFORMATION

Additional information Date of printing: 10.02.2017
Date of issue/Date of revision: 10.02.2017
Date of previous issue N/A
Version 1.0

Key to abbreviations

ADG = Australian Dangerous Goods
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
UN = United Nations

References : Not available

Report status The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

[End of SDS]