

PLATINUM

High Gloss



TECHNICAL DATA SHEET



TYPICAL PHYSICAL PROPERTIES

Colour:	Milky white opaque emulsion	
Solvent type:	100 / xylene	
% Nonvolatile:	Weight*	23.0 – 25.0
	Volume*	21.2 - 23.0
	Specific Gravity	0.92
	Viscosity Brookfield LVT (sp1/30rpm/25°C)	40-70 cps
	Flash point (°C)	24
	Tg* (°C)	45

*Theoretical values are listed. Actual values may vary depending on test method and coating composition.

DESCRIPTION

Platinum High Gloss acrylic solution is a modification of our widely used Durasol 310 that has been internally modified to give a more flexible film. It produces hard, very flexible, but highly durable coatings with excellent gloss retention and is ideally suited for use in clear or pigmented coatings on a variety of substrates. Applications include concrete and masonry protection, slate sealers and coatings for pavers. The product is supplied as a 24% solution in a blend of Solvent 100 and xylene. Manufactured in Thailand.

FEATURES

- Produces highly durable, hard coatings
- Ideal for use in clear or pigmented coatings on a variety of substrates
- Formulated for general purpose concrete and masonry protection, slate sealers and coating for pavers
- Compatible with a wide range of industrial solvents

PERFORMANCE BENEFITS

- Excellent gloss retention
- Excellent resistance to weathering
- Non-yellowing
- Very flexible

DISCLAIMER

The information provided herein was believed by Premium Sealers specialty chemicals ("Premium Sealers") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Premium Sealers are subject to Premium Sealers's terms and conditions of sale. Premium Sealers makes no warranty, express or implied, concerning the product or the merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided by Premium Sealers, except that the product shall conform to Premium Sealers's specifications. Nothing contained herein constitutes an offer for the sale of any product.

REGISTERED OFFICE

Unit 1/5 Edison Circuit, Forrestdale, WA 6112
Technical advice or SDS
email: ask@sealers.com.au or call 1800 779 007