

TECHNICAL DATA SHEET



TYPICAL PHYSICAL PROPERTIES

Colour:	Clear, colourless, viscous liquid	
Solvent type:	xylene	
% Nonvolatile:	Weight*	24.0 - 26.0
	Volume*	21.9 - 23.8
	Specific Gravity	0.915
	Viscosity Brookfield LVT (sp1/30rpm/25°C)	30-50 cps
	Flash point (°C)	24
	Tg* (°C)	29

*Theoretical values are listed. Actual values may vary depending on test method and coating composition.

DESCRIPTION

Platinum Same Day Seal is a low odour acrylic solution that produces a durable and very flexible clear film. It has excellent resistance to water, alkalis, weathering and UV light and is specifically designed as a sealant for “wet on wet” application in the manufacture of concrete roof tiles. The product is supplied as a 25% solution in xylene. Manufactured in Thailand.

FEATURES

- Designed for “wet on wet” application in the manufacture of concrete roof tiles
- Excellent resistance to water and alkalis
- Compatible with a wide range of industrial solvents
- Compatible with most phthalate and phosphorus plasticizers.

PERFORMANCE BENEFITS

- Protects against efflorescence – a common problem experienced in new concrete products
- Excellent exterior durability
- Excellent resistance to UV light
- Can be used for non-roof tile applications, including general purpose concrete and masonry coating

DISCLAIMER

The information provided herein was believed by Premium Sealers specialty chemicals (“Premium Sealers”) to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Premium Sealers are subject to Premium Sealers’s terms and conditions of sale. Premium Sealers makes no warranty, express or implied, concerning the product or the merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided by Premium Sealers, except that the product shall conform to Premium Sealers’s specifications. Nothing contained herein constitutes an offer for the sale of any product.

REGISTERED OFFICE

Unit 1/5 Edison Circuit, Forrestdale, WA 6112

Technical advice or SDS

email: ask@sealers.com.au or call 1800 779 007